

PAM RAPID replaces PAM CV & CE couplings



PAM CV - CE COUPLINGS WILL BE DISCONTINUED

We are putting an end to PAM CV - CE two-screw couplings in building construction as they do not comply with the current fire protection laws. Production has therefore been discontinued and PAM RAPID will replace PAM CV - CE.

One-screw couplings are always the first choice for safe and fast connections. PAM RAPID couplings are fast to install and fully compliant with latest regulations for cast-iron drainage pipes and are also suitable for renovation.

Starting from first of January 2022, we will stop commercialisation of PAM CV - CE couplings, please check for stock availability.

PAM RAPID HAS IT ALL!

- ✓ Fire reaction performance: tested & approved
- ✓ Compliant with standard EN877
- ✓ Large range from DN 50 to DN 300
- ✓ Super-fast single bolt installation
- ✓ High stability in the pipe system
- ✓ Full opening strap particularly suited to renovation projects

HOW TO INSTALL PAM RAPID?

• DN 50 TO DN 200 ASSEMBLY AS A SLEEVE

Couplings are supplied pre-assembled. The PAM RAPID from DN 50 to DN 200 is designed to be tightened to fully closed, there is no need to check the torque.

• DN 250 TO DN 300

They can be assembled in two different ways, depending on whether an open strap is required.

FOR INSTALLATION DETAILS YOU CAN WATCH OUR TUTORIALS ON SAINT-GOBAIN PAM SOIL & DRAIN YOUTUBE CHANNEL



TECHNICAL INFORMATION



Standard version W2

technical specifications:

- > Strap, clamps:
1.4510 /11 (AISI 430Ti / 439)

All stainless steel version W5

technical specifications:

- > Strap, clamps:
1.4404 / 1.4571 (AISI 316 L/316Ti)
- > Screw and nut: austenitic
stainless steel A4-70 or AISI 316

PAM RAPID-S / PAM RAPID INOX

DN	L	H	W	Weight	PAM RAPID-S	PAM RAPID INOX
					W2	W5
50	70	80	42	0.1	210424	185635
75	90	103	42	0.12	210426	207819
100	125	139	48	0.18	210427	185636
125	147	161	56	0.28	210428	207820
150	172	187	56	0.32	210429	207831
200	223	240	70	0.6	210430	185637
250	290	315	95	1.1	228759	228773
300	350	375	95	1.25	228771	228775

The PAM Rapid is designed for full tightening with "zero gap", there is no need to check the torque. For DN 250 and 300, apply the following torque: 25 N.m.

PAM RAPID WITH NBR GASKET (NITRILE COUPLING)

DN	L	H	W	Weight	PAM RAPID NBR GASKET
					W5
50	70	80	42	0.1	212705
75	90	103	42	0.12	212708
100	125	139	48	0.18	212709
125	147	161	56	0.28	212710
150	172	187	56	0.32	212711
200	223	240	70	0.6	212712
250	290	315	95	1.1	212713
300	350	375	95	1.25	212714

For wastewater liable to contain hot oil, solvents or hydrocarbons, it is recommended to use **couplings equipped with specific NBR gaskets.**

"All dimensions are in mm and nominal weights are in kg"



Saint-Gobain PAM Bâtiment